



Sustainability

Data for building certification systems

| Deutsche Gesellschaft für Nachhaltiges Bauen e.V. (German Sustainable Building Council, DGNB for short) | | |
|---------------------------------------------------------------------------------------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ENV1.2, Version 2018 | Product group: | No. 2: Coatings mainly on mineral substrates in interiors (decorative paints, primers, decorative fillers) |
| | Quality level: | Meets quality level 2 – VOC content < 30 g/l (in accordance with Directive 2004/42/CE) |
| | Product group: | No. 5: Coating materials for mineral surfaces in exteriors |
| | Quality level: | Meets quality level 4 – VOC content < 40 g/l (in accordance with Directive 2004/42/CE) |
| ENV1.2, Version 2023 | Product group: | No. 2: Coatings mainly on mineral substrates in interiors (decorative paints, primers, decorative fillers, as well as deep-acting primers, floor coatings without any special resistance requirements, concrete lasures) |
| | Quality level: | Meets quality level 2 – VOC content < 30 g/l (in accordance with Directive 2004/42/CE) |
| | Product group: | No. 5: Coating materials for mineral surfaces in exteriors |
| | Quality level: | Meets quality level 4 – VOC content < 40 g/l (in accordance with Directive 2004/42/CE) / without film protection |

| Qualitätssiegel Nachhaltiges Gebäude (German Quality Label for Sustainable Building, QNG for short) | | |
|-----------------------------------------------------------------------------------------------------|----------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Annex document 313 dated 14 September 2023 | Product group: | No. 5.3: Coatings on mineral surfaces (concrete, masonry, screed, cement slabs, gypsum plasterboard, plasters, and nonwovens) in interiors |
| | Quality level: | Met – VOC ≤ 30.0 g/l (water-based formulation) |
| | Product group: | No. 5.2: Facade paints incl. primers |
| | Quality level: | Met – VOC ≤ 30.0 g/l (water-based formulation), biocidal substances declaration (if used), and lead compounds ≤ 0.10 % |

Priming coat**Qualitätssiegel Nachhaltiges Gebäude (German Quality Label for Sustainable Building, QNG for short)**

| | |
|---------------------------------------------------------------------------------------------------------------|-------------------------------------------|
| Proposal for assignment: LCA calculation values for QNG Sustainable Building Certification | 8.9 Undercoat, interior (synthetic resin) |
|---------------------------------------------------------------------------------------------------------------|-------------------------------------------|

Bewertungssystem Nachhaltiges Bauen (German Assessment System for Sustainable Building, BNB for short)

| | | |
|---------------------------------------|----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| BNB_BN 1.1.6, Version 2015 | Product group: | No. 4: Fillers, binding coatings, primers |
| | Quality level: | Meets quality level 3 – Water-based only: VOC < 30g/l |
| | Product group: | No. 6a: External wall paints incl. primers |
| | Quality level: | Meets quality level 5 – VOC < 20 g/l and no use of biocide agents except in-can preservatives and no pigments and driers based on lead, cadmium, and chromium (VI) compounds |

Minergie-ECO / ecobau

| | | |
|------------------------------|--------------------------|------------|
| Ecobau classification | Swiss environment label: | B |
| | Report number: | ECO-CH-121 |
| | Ecobau: | |
| | Ecobau: | |
| | Ecobau: | |
| | Report number: | |

Leadership in Energy and Environmental Design (LEED v. 4.1)

| | | |
|------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|
| VOC content (EQ Credit: Low-emitting materials) | 1 g/l Calculated in accordance with the Decopaint Directive 2004/42/CE Met in accordance with LEED v4 | |
| VOC emissions (EQ Credit: Low-emitting materials) | Limit value: | In accordance with the Committee for Health-related Evaluation of Building Products (AgBB Germany) |

Leadership in Energy and Environmental Design (LEED v. 4.1)

| | | |
|-----------------------------------------------------------------------------------------------------|---------------------------------------|----------------------------------------------------------------------------------------------------|
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| SVOC emissions (EQ Credit: Low-emitting materials) | Limit value: | In accordance with the Committee for Health-related Evaluation of Building Products (AgBB Germany) |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| Formaldehyde emissions (EQ Credit: Low-emitting materials) | Limit value: | $\leq 0.01 \text{ mg/m}^3$ |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| Recycling percentage (post-consumer recycled content) (MR Credit: Sourcing of raw materials) | 0 % | |
| Recycling percentage (pre-consumer recycled content) (MR Credit: Sourcing of raw materials) | 0 % | |
| Renewable raw materials (bio-based materials) (MR Credit: Sourcing of raw materials) | 0 % | |

Building Research Establishment Environmental Assessment Method (BREEAM)

| | | |
|------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|-----------------------------|
| VOC content (EQ Credit: Low-emitting materials) | 1 g/l Calculated in accordance with the Decopaint Directive 2004/42/CE Met in accordance with BREEAM | |
| VOC emissions (Hea 02: indoor air quality) | Limit value: | $\leq 0.3 \text{ mg/m}^3$ |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| SVOC emissions (Hea 02: indoor air quality) | Limit value: | |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| Formaldehyde emissions (Hea 02: indoor air quality) | Limit value: | |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| CMR emissions (Hea 02: indoor air quality) | Limit value: | $\leq 0.001 \text{ mg/m}^3$ |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |

EU Taxonomy Regulation (EU) 2020/852

| | | |
|---------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|---------------------------|
| Compliant with Annex C | Met | |
| Note | This statement is based on the formulation data of Sto SE & Co. KGaA and information from our upstream suppliers. | |
| Formaldehyde emissions | Limit value: | |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| Other carcinogenic VOCs in categories 1A and 1B (CMR) | Limit value: | ≤ 0.001 mg/m ³ |
| | Degree to which requirements are met: | Met |
| | Test institute: | TÜV SÜD |
| | Report type: | Individual audit report |
| | Report number: | 24-S1428-81 |
| Compliant with minimum social requirements (human rights, German Supply Chain Due Diligence Act, etc.) | https://www.sto.de/s/unternehmen/compliance | |

Eco-labels and environmental labels

| | | |
|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|------------|
| Eco-label, certificates | | |
| ISO certification 9001, 14001, 50001 | https://www.sto.de/s/unternehmen/managementsysteme | |
| Environmental Product Declaration (EPD) | EPD-VDL:20240612-IBN1-DE | |
| Product-specific working life (in accordance with BNB service life table) | Years: | > 50 years |
| | Application range: | Interiors |
| | Years: | > 50 years |
| | Application range: | exterior |

Eco-label, certificates

| | | |
|---------------------------------------------------------------|----------------------|------------|
| Product-specific working life (in accordance with EPD) | Years: | > 50 years |
| | Application range: | Interiors |
| | Years: | > 50 years |
| | Application range: | exterior |
| GISCODE | See SDS (section 15) | |

Product ingredients

| | | |
|-----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|---------------------------------|
| Organic component (in accordance with natureplus / baubook) | >5% | |
| Hazardous substances (in accordance with EU regulations) | See SDS (section 3) | |
| CMR substances (VOC) | Cannot be determined (limit of quantification: 1 mg/kg) (in accordance with DIN EN ISO 17895) | |
| VOC content (in accordance with Directive 2004/42/CE) | <1 g/l | |
| Solvent (in accordance with VdL Directive 01) | Content: | < 700 mg/kg Solvent-free |
| | Base: | See test report |
| Plasticiser (in accordance with VdL Directive 01) | Content: | < 500 mg/kg Plasticiser-free |
| | Base: | See test report |
| Free formaldehyde (in accordance with VdL Directive 01) | Content: | < 2 mg/kg Formaldehyde-free |
| | Base: | See test report |
| Biocide(s), active substance(s) for protection of the coating (in accordance with Regulation (EU) No 528/2012) | Not present | |

Priming coat

| | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|-----------------|
| Biocide(s), active substance(s) for protection of the product during storage (in accordance with Regulation (EU) No 528/2012) | Present, see SDS (section 2) | |
| Heavy metals | <1 mg/kg for heavy metal | |
| | (Migration in accordance with EN 71-3) | |
| Compliant with the emissions restrictions of the titanium dioxide industry (in accordance with Directive 2010/75/EU and 25th Ordinance for the Implementation of the Federal Immission Control Act) | Yes | |
| SVHC in accordance with the REACH chemicals regulation (EC/1907/2006), Annex XIV | Content: | <0,1% |
| | Base: | See test report |

Carbon footprint

| | |
|---------------------------------------------------------------|----------------------------------|
| A1-A3 (cradle to gate – manufacturing) | 0.711 kg CO ₂ e / kg |
| A4 (transport from manufacturer to site) | 0.282 kg CO ₂ e / kg |
| A1-C4 (cradle to grave – life cycle) | 1.036 kg CO ₂ e / kg |
| D (Benefits and loads beyond the system boundary) | -0.016 kg CO ₂ e / kg |
| A1-D (cradle to cradle – life cycle including benefit) | 1.02 kg CO ₂ e / kg |

Disposal, reuse, recycling

| | |
|----------------------------------|--------------------------------------------------|
| Recycling of site residue | Correctly sorted, clean material can be recycled |
| | See SDS (section 13) |

Priming coat

| | |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Recycling of dismantled building material | Can be reworked |
| | See Environmental Product Declaration (EPD) |
| Recycling of packaging material | Can be reused or recycled |
| | See https://www.sto.de/s/service-tools/entsorgung |
| Circular economy at Sto | https://www.sto.de/s/nachhaltigkeit/kreislaufwirtschaft |

Corporate responsibility at Sto

| | |
|------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Guiding principles, management of the company | Sto's vision is to be the technology leader in the sustainable design of living space tailored to human needs. Worldwide. For further information please visit: www.sto.com |
| UN Global Compact - membership | Sto is a member of the UN Global Compact and is committed to upholding ten universally acknowledged principles taken from the areas of human rights, labour standards, environmental protection, and anti-corruption. For further information please visit: www.unglobalcompact.org |
| Supplier code of conduct | https://www.sto.de/cepcom/de/Dokumente/Unternehmen/Lieferanten/Sto-Supplier-Code-of-Conduct_01_12-23-(1).pdf |

Notes

| | |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version | 03 |
| Creation and use | The information and data contained in this sustainability data sheet is based on our knowledge and experience. The publication of a new sustainability data sheet invalidates all previous versions. Please observe the information in the Technical Data Sheet and Safety Data Sheet. The latest version is available on the Internet. Formulations are subject to change! |

Headquarters

Sto SE & Co. KGaA, Ehrenbachstraße 1, 79780 Stühlingen

Infoservice

+49 7744 57-1010, infoservice@sto.com, www.sto.de